

AVKOPACK® 1120**CHARACTERISTICS**

Gland packing braided by PTFE - graphite yarn, impregnated with a special lubricant. The graphite is incorporated in the yarn, thus making the packing clean when touched.

APPLICATION

AVKOPACK® 1120 is used for the sealing of pumps, mixers, valves, and sliders. The packing is applicable in all chemical environments but mainly used for sealing chemical aggressive environments, water and steam up to 280 °C.

The fields of usage are in sealing installations and equipment in the chemical, pharmaceutical, oil refining and food processing industries, especially in the chemical departments of the power supplying industry, etc. Due to the graphite the packing has very good heat conductivity, which determines the possibility to be used for sealing shafts in high-motion pumps with high speed in the peripheries.

ADVANTAGES

AVKOPACK® 1120 is suitable to be used both for acids and for bases. The packing has a very low shrinkage, does not lose volume, it is very flexible, does not grow old, and does not get fragile.

TECHNICAL PARAMETERS

Working temperature:	-100 °C / +280 °C
Working pressure:	
- for rotary - pumps:	30 bar
- for piston - pumps	80 bar
- for armature:	200 bar
pH:	0 – 14
V	20 m/s
Standard dimensions:	from 4 x 4 mm to 26 x 26 mm

HEALTH HAZARD INFORMATION: No harmful effects ascertained.

The information listed in this technical data sheet is based on our company's trials and experience. AVKO jsc is not to be held responsible for poor installation or application in media combining complexity of factors whose total exceeds the general qualities of the product. Our technical and sales representatives will assist any client in need of a product with a peculiar application.