

AVKOPACK® 1201 PD**CHARACTERISTICS**

Gland packing with guaranteed quality manufactured from high technology raw materials and yarns using up-to-dated production technology.

AVKOPACK® 1201 PD is braided from dry staple aramide yarn.

APPLICATION

AVKOPACK® 1201 PD is used for sealing of armature, flanges, static sealing, etc. It is especially useful for work under extremely high pressure.

It is widely applied for sealing of devices and equipment in the glass industry, petrol industry, chemical, etc.

ADVANTAGES

The main material used for the production of this packing – staple aramyde fiber – is a synthetic fiber characterized with excellent strength. It has very good properties for work under pressure and wearing reistance

This packing guarantees long exploitation term and keeps the environment from being polluted.

TECHNICAL PARAMETERS

Working temperature:	-100 °C / +280 °C
Working pressure:	
- for rotary - pumps:	-
- for piston - pumps	-
- for armature:	250 bar
pH:	1 – 13
V	-
Standard dimensions:	from 4 x 4 mm to 25 x 25 mm

HEALTH HAZARD INFORMATION

No harmful effects ascertained.

The information listed in this technical data sheet is based on our company's trials and experience. AVKO jsc is not to be held responsible for poor installation or application in media combining complexity of factors whose total exceeds the general qualities of the product. Our technical and sales representatives will assist any client in need of a product with a peculiar application.